

Imagine.

DVE
Digital Value Engineering

Roland[®]



Bringing print and cut to the desktop



VersaSTUDIO
BN-20



Mobile Phone and Laptop Wraps

Roland Print&Cut versatility allows you to print and digitally die cut graphics in one seamless workflow for custom labels and decals, including mobile phone skins, laptop wraps and more.



Heat Transfers for Garments

Right at your desktop, you can print quality heat transfers and contour cut them into any shape for stylish results. Apply Metallic Silver ink for hundreds of striking metallic colour effects.*1

POS and POP

With the BN-20, you can produce POP displays in unique shapes and colours that attract attention and drive retail sales. Create a single POP or an entire campaign, profitably, with all the convenience of our easy-handling 220cc ink cartridges.

Explore a World of New Applications Right at Your Desktop

Print&Cut Versatility • Outdoor Durable Inks • Metallic Effects

With a Roland VersaSTUDIO BN-20 20-inch inkjet printer/cutter, the possibilities are endless. This powerful, yet compact printer includes everything you need to print and cut high quality durable graphics right at your desktop. Add stunning metallic effects, perfect for premium brands. Display your graphics indoors or out for lasting impact. A complete low-cost solution, the BN-20 is a great investment for your growing business.

Cut Vinyl Signage

From pinstriping for vehicles and motorcycles to window signs and displays, contour cutting is essential to your production workflow. The BN-20 allows you to cut vinyl signs using a wide variety of fonts*.

*The BN-20 supports TrueType and OpenType fonts.

Labels and Decals for Outdoor Display

The BN-20 comes with award-winning Roland ECO-SOL MAX ink for outdoor signs, labels and decals. Graphics are easy to produce and durable up to three years outdoors without lamination.*2 The BN-20 also supports water-based Roland FPG inks for exceptional indoor graphics.*3




Posters

Using Metallic Silver ink, you can add luxurious accents and premium value to posters and photographic reproductions.




A Complete Solution


The BN-20 allows you to print graphics up to size A2 or 480 mm wide (18.9"), including crop marks for easy finishing. Featuring its own print management and design software, the BN-20 is a complete business solution in a box.



VersaSTUDIO
BN-20



*1 Metallic silver ink should only be used on garments as a spot colour as mixing it with other colours will negatively impact washability.
*2 Three year outdoor durability is based on accelerated weather tests conducted by Roland DG. Results may vary depending on the location and application. Some applications, including vehicle graphics, may require lamination.
*3 Ink type must be selected at the time of purchase.



Roland VersaWorks® supports Adobe® Illustrator®, CorelDRAW® and other popular design software packages. Choose from a wide variety of layout functions including scaling, cropping, rotating, auto layout and tiling to optimise your print media. VersaWorks also features Roland Color System Libraries for accurate colour matching of traditional and metallic colour, and variable data printing which allows you to efficiently create a series of signs, labels and name badges in which the text and graphics change from one print to the next.



Roland VersaWorks System Requirements

Operating system	Windows® 7 Professional/Ultimate (32-bit); Windows Vista® Business/Ultimate (32-bit); Windows® XP Professional Service Pack 2 or later (32-bit)
CPU	Core™ 2 Duo, 2.0 GHz or faster recommended
RAM	2 GB or more recommended
Video card and monitor	A resolution of 1,280 x 1,024 or more recommended
Free hard-disk space	40 GB or more recommended
Hard-disk file system	NTFS format
Optical drive	DVD-ROM drive

Application software compatible with Cutting and Print&Cut

Adobe® Illustrator® 10, CS, CS2, CS3, CS4, CS5 / CorelDRAW® 11, 12, X3, X4, X5

R-Works Easy-To-Use Roland Design Software Included

R-Works allows you to immediately start designing graphics for the BN-20, even if you do not have any design software of your own. With R-Works, you can quickly import commercially-available stock photos or personal photos taken with a digital camera. Create original layouts with text and graphics for custom T-shirts, labels and decals.



R-Works System Requirements Windows® 7 Professional/Ultimate (32-bit); Windows Vista® Business/Ultimate (32-bit); Windows® XP Professional Service Pack 2 or later (32-bit)

Specifications		
Printing technology	Piezoelectric inkjet	
Media	Width	150 to 515 mm (5.9 to 20.3 in.)
	Thickness	Maximum 1.0 mm (39 mil) with liner, for printing Maximum 0.4 mm (16 mil) with liner and 0.22 mm (9 mil) without liner, for cutting
	Roll outer diameter	Maximum 150 mm (5.9 in.)
	Roll weight	Maximum 6 kg (13.2 lbs.)
	Core diameter	76.2 mm (3 in.) or 50.8 mm (2 in.)
Printing/cutting width*1	Maximum 480 mm (18.9 in.)	
Ink cartridges	Type and capacity	Roland ECO-SOL MAX (220 cc cartridge) or Roland aqueous pigment (FPG) ink (220 cc cartridge)
	Colours	Five Colours (cyan, magenta, yellow, black, and metallic silver) or Four Colours (cyan, magenta, yellow, and black) (Five Colours are only ECO-SOL MAX)
Printing resolution (dpi)	Maximum 1,440 dpi	
Cutting blade	Type	Roland CAMM-1 series compatible
	Blade offset	0.25 mm (9 mil)
Cutting speed	10 to 150 mm/s	
Blade force	30 to 300 gf	
Software resolution (when cutting)	0.025 mm/step	
Distance accuracy (when printing) *2 *3	Error of less than ±0.3% of distance traveled, or ±0.3 mm, whichever is greater	
Distance accuracy (when cutting) *2 *4	Error of less than ±0.4% of distance traveled, or ±0.3 mm, whichever is greater	
Repetition accuracy (when cutting) *2 *5	±0.1 mm or less	
Alignment accuracy for printing and cutting *2 *6	±0.5 mm or less	
Alignment accuracy for printing and cutting when reloading media *2 *7	Error of less than ±0.5% of distance traveled, or ±3 mm, whichever is greater	
Print heater *8	Temperature: 35°C (95°F)	
Connectivity	USB (compliant with Universal Serial Bus Specification Revision 2.0)	
Power-saving function / Power requirements	Automatic sleep feature / AC 100 to 240 V ±10 %, 1.5 A, 50 / 60 Hz	
Power consumption	During operation	Approx. 90 W
	Sleep mode	Approx. 5.5 W
Acoustic noise level	During operation	62 dB (A) or less
	During standby	42 dB (A) or less
Dimensions / Weight	995 (W) x 585 (D) x 291 (H) mm (39.2 (W) x 23 (D) x 11.5 (H) in.) / 35 kg (79.4 lbs.)	
Environmental	Power on	Temperature: 20 to 32°C (68 to 90°F), humidity: 35 to 80%RH (no condensation)
	Power off	Temperature: 5 to 40°C (41 to 104°F), humidity: 20 to 80%RH (no condensation)
Included items	Power cord, USB cable, blade, blade holder, Roland Software Package, Software RIP (Roland VersaWorks), User's Manual, etc.	

Options	Model	Description
ECO-SOL MAX Ink	ESL3-MG	Magenta, 220 cc
	ESL3-YE	Yellow, 220 cc
	ESL3-CY	Cyan, 220 cc
	ESL3-BK	Black, 220 cc
	ESL3-MT	Metallic silver, 220 cc
Aqueous Pigment Ink	SL-CL	Cleaning liquid, 1 pc.
	FPG-MG	Magenta, 220 cc
	FPG-YE	Yellow, 220 cc
	FPG-CY	Cyan, 220 cc
	FPG-BK	Black, 220 cc
	CJ-CL	Cleaning liquid, 1 pc.
Blade	ZEC-U5022	For thick, reflective and fluorescent vinyl, 2pcs.
Blade holder	XD-CH3	Blade holder with blade extension adjuster, made of resin



PNS-24
Optional Stand

*1 The length of printing or cutting is subject to the limitations of the program. *2 Using Roland specified media, loaded correctly, temperature: 25°C (77°F), humidity: 50 %RH, all pinch rollers are used, 25 mm or more for both right and left margins and 35 mm or more front margin, excluding expansion or contraction of the media, and all correction and adjustment functions of this machine have been made properly. *3 Using Roland specified media, print travel of 1m. *4 Using Roland specified media, cut travel of 1m. *5 Range for assured repetition accuracy: Length 1,000 mm *6 Provided that media length is under 1,000 mm. Excluding possible shift caused by expansion/contraction of the media and/or by reloading the media. *7 Using Roland specified media, data size: 1,000 mm in the media-feed direction, 480 mm in the carriage-movement direction. No lamination. Automatic detection of crop marks at 4 points when media is reloaded. Excludes the effects of skewed movement and of expansion and contraction of the media. *8 Warm-up is required after power up. This may require 5 to 20 minutes, depending on the operating environment. The preset temperature may fail to be reached 35°C (95°F) depending on the ambient temperature and media width.

About Metallic Silver Ink

Due to the nature of the metallic silver ink, the pigment in this ink will settle in the cartridge and ink flow system, requiring you to shake the cartridge before each use. Outdoor durability is three years for CMYK inks, one to three years for metallic silver ink, depending on the media used. Roland strongly recommends lamination for both indoor and outdoor graphics to ensure the quality of metallic silver ink.

Roland DG products that feature this environmental label meet the company's criteria for environmental consciousness, a set of standards based on ISO 14021 self-declaration type II. For more information, please visit www.rolanddg.com.



ISO 14001:2004 and ISO 9001:2008 Certified

Roland pursues both environmental protection and continuous quality improvement. Under the philosophy of preserving the environment and human health, Roland is actively working to abolish organic solvents in production, to reduce and recycle waste, to reduce power use, and to purchase recycled products. Roland constantly strives to provide the most highly reliable products available.



Roland reserves the right to make changes in specifications, materials or accessories without notice. Your actual output may vary. For optimum output quality, periodic maintenance to critical components may be required. Please contact your Roland partner for details. No guarantee or warranty is implied other than expressly stated. Roland shall not be liable for any incidental or consequential damages, whether foreseeable or not, caused by defects in such products.

Adobe, PostScript, PostScript 3 and the PostScript logo are trademarks of Adobe Systems Incorporated. All other trademarks are the property of their respective owners. Roland DG Corp. has licensed the MMP technology from the TPL Group.